

# Ashcroft® Control Instruments Switch Specification Sheet

Pressure

Differential Pressure

Temperature

## FUNCTIONAL INFORMATION:

Single setpoint, (1) SPDT switch.

Single setpoint, (2) SPDT switches (DPDT).

Dual setpoints, independently adjustable.

Setpoint #1: \_\_\_\_\_ Incr.      Decr.      (circle one)

Setpoint #2 (if required): \_\_\_\_\_ Incr.      Decr.      (circle one)

Maximum system pressure: \_\_\_\_\_

If Differential Pressure, what is STATIC WORKING PRESSURE: \_\_\_\_\_

Fixed deadband of \_\_\_\_\_

Adjustable deadband

## ELECTRICAL SPECIFICATIONS:

What is the switch element connected to: \_\_\_\_\_

Voltage: \_\_\_\_\_ AC    DC    Current: \_\_\_\_\_ mA    A

## ENCLOSURE:

Watertight, Nema 4X

Explosion proof, Nema 7,9

## PROCESS INFORMATION:

¼ NPT Female

½ NPT Female

½ NPT Male

What is the media: \_\_\_\_\_

Temperature of media: \_\_\_\_\_ °F    °C    (circle one)

TEMP. SWITCHES ONLY:       Remote Mount       Direct Mount



# Fax

To:	Centro, Inc.	From:	
Fax:	901-357-1379	Pages:	
Phone:	800-344-3286	Date:	
Re:		cc:	

Please fill out this specification form and fax to one of the three locations:

Memphis: 901-357-1379

Little Rock: 501-835-2277

Nashville: 615-255-2212