

DISTRIBUTOR INFORMATION

Distributor Name/Contact Person: _____

CUSTOMER INFORMATION

Customer Name: _____

Customer Address: _____

Contact Name/Telephone: _____

APPLICATION DATA

Service: Meter to be used for: Rate of Flow Indication _____ Totalization _____ Batching _____
Process Control _____ Other _____

Product (process fluid): _____

Conductivity of Product: _____ (5 μ S/cm minimum)

Suspended Solids in Product? _____ Fluid Abrasive? _____

Flow Rate (GPM): Min _____ Max _____ Normal _____

Pressure Rating (psi): Max _____

Temperature Range (F): Min _____ Max _____ Normal _____

Process Fittings (flanged, wafer, threaded, sanitary) _____

Pulse Output/unit: _____ (pulses per unit must not exceed 2.5kHz at max flow or 10kHz with Converter Option "D" High Frequency Output)

Desired Display (if specified on converter): Totalizer Units _____ (full gal., 1/10th gal, etc)
Rate of Flow Units _____ (full gpm, 1/10th gpm, etc.)Analog Output Range: 0 - 20mA _____ or 4 - 20mA _____
0 or 4 mA = _____ GPM
20mA = _____ GPM

Supply Voltage: _____ VAC or _____ VDC

Converter Location: Integral _____ Remote _____

Length of Cable Required: _____ ft.



Fax

To: Centro, Inc.	From:
Fax: 901-357-1379	Pages:
Phone: 800-344-3286	Date:
Re:	CC:

Please fill out this specification form and fax to one of the three locations:

Memphis: 901-357-1379

Little Rock: 501-835-2277

Nashville: 615-255-2212